

Applic. No.: 08/930,735  
Amdt. Dated December 23, 2003  
Reply to Office action of October 16, 2003

Amendments to the Claims:

) This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

Claim 1 (currently amended): A device for avoiding or limiting the tilting of the head forwards and/or to the side of a passenger sitting in a seat with a backrest, comprising:

at least one one-piece or multi-piece head-support element including one or more cushion-shaped elements, said one or more cushion-shaped elements being configured and dimensioned for, in an intended use position, completely surrounding the side and front sections of the neck and/or of the head of the passenger, resting on the shoulders and/or the chest region of the passenger; and

) a one-piece or multi-piece connecting section for holding said head-support element in said intended use position, said head-support element continuing into said connecting section, said connecting section being configured and dimensioned for guiding over and beyond the backrest of the seat and/or being suspended around or over a headrest provided on the seat by throwing said connecting section over the backrest or around

Applic. No.: 08/930,735  
Amdt. Dated December 23, 2003  
Reply to Office action of October 16, 2003

or over the headrest, said connecting section being formed by two flexible-support elements.

Claim 2 (cancelled).

Claim 3 (previously amended): The device according to claim 1, wherein said head-support element is connected via said connecting section to at least one weight element, said head support element, said connecting section and/or said weight element are configured for said weight element to rest or hang behind the passenger.

Claim 4 (previously amended): The device according to claim 3, wherein said weight element is substantially formed by sand which is filled into one or more chambers.

Claim 5 (previously amended): The device according to claim 1, wherein said head-support element is formed by cushion-shaped elements which are of elongate shape.

Claim 6 (previously amended): The device according to claim 1, wherein said cushion-shaped element or elements forming said head-support element have connecting devices which permit a releasable connection of said cushion-shaped elements to one another and/or a

Applic. No.: 08/930,735  
Arndt. Dated December 23, 2003  
Reply to Office action of October 16, 2003

releasable connection to said connecting section and/or to said weight element.

Claim 7 (cancelled).

Claim 8 (currently amended): ~~The device according to claim 1,~~  
wherein A device for avoiding or limiting the tilting of the  
head forwards and/or to the side of a passenger sitting in a  
seat with a backrest, comprising:

at least one one-piece or multi-piece head-support element  
including one or more cushion-shaped elements, said one or  
more cushion-shaped elements being configured and dimensioned  
for, in an intended use position, completely surrounding the  
side and front sections of the neck and/or of the head of the  
passenger, resting on the shoulders and/or the chest region of  
the passenger; and

a one-piece or multi-piece connecting section for holding said  
head-support element in said intended use position, said head-  
support element continuing into said connecting section, said  
connecting section being configured and dimensioned for guiding  
over and beyond the backrest of the seat and/or being suspended  
around or over a headrest provided on the seat by throwing said  
connecting section over the backrest or around or over the

Applic. No.: 08/930,735  
Amdt. Dated December 23, 2003  
Reply to Office action of October 16, 2003

) headrest, said connecting section ~~has~~ having connecting devices, which permit a releasable connection of parts of connecting sections to one another and/or a releasable connection to said head-support element and/or to said weight element.

Claim 9 (currently amended): ~~The device~~ Device according to claim 1, wherein A device for avoiding or limiting the tilting of the head forwards and/or to the side of a passenger sitting in a seat with a backrest, comprising:

at least one one-piece or multi-piece head-support element including one or more cushion-shaped elements, said one or more cushion-shaped elements being configured and dimensioned for, in an intended use position, completely surrounding the side and front sections of the neck and/or of the head of the passenger, resting on the shoulders and/or the chest region of the passenger; and

) a one-piece or multi-piece connecting section for holding said head-support element in said intended use position, said head-support element continuing into said connecting section, said connecting section being configured and dimensioned for guiding over and beyond the backrest of the seat and/or being suspended around or over a headrest provided on the seat by throwing said connecting section over the backrest or around or over the

01-14-'04. 16:22 FROM-

T-604 P07/10 U-873

Applic. No.: 08/930,735  
Amdt. Dated December 23, 2003  
Reply to Office action of October 16, 2003

)  
headrest, effective dimensions of said connecting section ~~can be~~  
~~varied~~ being variable by an adjustment mechanism or variable  
connection device.